



TECHNICAL DATA SHEET

Issue: 5-Jun-15

SILICONE 18 111

This product is an excellent long lasting repellent designed to penetrate concrete and masonry surfaces to prevent the ingress of water, dirt and grease.

FEATURES & BENEFITS

- * Maintains natural surface appearance
- * Easy to use
- * Controls moisture transmission
- * Prevents efflorescence
- * Repels dirt and fungus

PERFORMANCE GUIDE & COMPARISON*

Product	Ease of Application	Preparation	Durability	Maintenance
111	Easy to apply	Low	N/A	N/A

Characteristic	Typical Value
Colour	Clear natural look
Solids (vol. %)	<5%
Gloss	Low
Pack Sizes	20 Litre and 5 Litre
Abrasion Resistance	N/A
Chemical Resistance	N/A
Solvent Resistance	N/A

* Performance Guide & Comparison

Description	Evaluation and Meaning
Ease of Application	The level of effort and expenditure to apply the coating, combined with level of expertise. <i>High = very easy to apply; Medium = easy to apply; Low = presents challenges for inexperienced users.</i>
Preparation	The level of effort and expense for preparing the substrate for coating. <i>High = a high level of effort and expertise required for preparation; Medium = modest preparation required; Low = low to no preparation required.</i>
Durability	The expected performance under standard Australian conditions for weathering and temperature variation. <i>High = High level of durability under extreme conditions; Medium = meets or exceeds standard conditions; Low = meets standard conditions, but not expected to endure.</i>
Maintenance	The level of continued coating support, or re-coating to achieve the same level of performance. <i>High = a high level of effort and expenditure in cleaning, or re-coating the system; Medium = a modest level of effort and expenditure for cleaning to keep the coating looking good and performing well; Low = almost no effort to support the coating system after application.</i>



TECHNICAL DATA SHEET

Issue: 5-Jun-15

APPLICATION

Flood surface by broom, roller or spray and allow to penetrate. Spread excess (do not allow to pool).

Spread-rate:

	Minimum	Maximum	Typical
Theoretical Spread Rate (m ² /L)	1	5	3
Wet Film Thickness (µm)	N/A	N/A	N/A
Dry Film Thickness (µm)	N/A	N/A	N/A

Dry Times**

Substrate Temperature	5 C	10 C	20 C	30 C
Surface Dry (minutes)	N/A	N/A	N/A	N/A
Hard Dry (hours)	N/A	N/A	N/A	N/A
Recoat Time (hours)	N/A	N/A	N/A	N/A

** Drying times are generally related to air circulation, temperature, and film thickness. The figures given above are typical with good ventilation, typical film thickness and single coat application.

SURFACE PREPARATION

It is recommended that surfaces are clean (free from any dirt, grease or other foreign matter) and dry.

DIRECTIONS FOR USE

Thoroughly stir contents and flood the surface, then spread excess to avoid pooling. NO thinning is required.

SAFETY

This product contains flammable solvents. Keep away from heat and flame. No smoking. Provide adequate ventilation and wear protective clothing. Consult the Safety Data Sheet.

Failure to observe these precautions will void all warranties and guarantees for product performance. The manufacturer will take no responsibility for coatings, products, labour, corrective action, or compensation where there is evidence of a failure to abide by the manufacturer's directions.

CLEAN UP

All Purpose Thinners.

DISCLAIMER

Do not apply this product if there is uncertainty about application or surface preparation. This Product Data Sheet is to be used as a guide only; it is NOT a specification.