

## PRODUCT DATA SHEET

---

### 444 CRACK REPAIR

#### Description:

A general use cement based crack repair to be used on most concrete and masonry surfaces.

Suitable to used internally or on externally surfaces. Ensure surface is clean and sound prior to applying.

Mix fresh clean water to a consistent paste to suit application. In general 1 Kg of 444 Crack repair to 200ml of water.

Use the mixed product up within 30 minutes at 23°C.

Will dry after 14 days to 35 MPa. Wash over with a damp sponge if a smoother finish is required.

**Thinning** N.A

**Equipment** General patching trowel equipment

**Coverage** 1kg at 10 mm deep x 10 mm wide will cover approx 5 lineal metres

**Drying Times** Dust Free:  
Touch Dry: 1 Hour  
Hard Dry: Overnight

<b>Container Sizes</b>	1 kg and 20 kg
<b>Cleaning</b>	Wash Up with Water
<b>Shelf Life</b>	Under normal conditions containers can be stored for up to 12 months before use.
<b>Precautions</b>	Advisable using gloves when handling
<b>Classification</b>	N.A

---

Paintec Pty Ltd  
26 Dulwich Street  
Loganholme Qld 4114

Phone (07) 38060600

---

Due to differences in substrates, application methods and local conditions purchasers of this product must ensure that it is suitable for their specific application. Information contained in this Data Sheet is subject to Paintec standard terms and conditions of sale.